

CRAMMIX BRICKS

Quality Clay Bricks since 1947



HOME | ABOUT US | **PRODUCTS** | MANUFACTURING | GALLERY | SUSTAINABILITY | EXPORTS | FAQ'S | LINKS | DOWNLOADS | NEWS | CONTACT

OUR PRODUCTS THE LANGUAGE OF CLAY BRICKS



- **Language of Bricks**
- Plaster Products
- Wine Cooler
- Special Shaped Bricks
- Face Bricks
- Handmade Cobbles
- Pool Copings
- Paving Bricks

FBS

FBS: FACE BRICK STANDARD

Clay bricks that are selected or produced for their durability and uniformity of size and shape.

NFP

NFP: NON-FACING PLASTERED

Clay bricks suitable for general building work that is to be plastered.

FBX

FBX: FACE BRICK EXTRA

Clay bricks that are selected or produced for their durability and high degree of uniformity of size, shape and colour.

NFX

NFX: NON-FACING EXTRA

Clay bricks suitable for use, plastered or unplastered, for general building work below damp-proof course or under damp conditions or below ground level where durability rather than aesthetics is the criterion for selection.



Environmentally Friendly

FBA

FBA: FACE BRICK AESTHETIC

Clay bricks that are selected or produced for their durability and aesthetic effect deriving from non-uniformity of size, shape or colour.

E

E: ENGINEERING UNITS

Masonry unit produced for structural or load-bearing purposes in face or non-face work, where the manufacturer supplies clay bricks to an agreed compressive strength. An engineering unit is designated by the addition of the letter E followed by the number equal to the nominal compressive strength in Mpa, eg. FBSE21.

Quality Standards

Certificates:

SABS Certificate
SABS ISO 9001

PA

PA: CLAY PAVERS

Clay pavers that are selected or produced for their durability and for a high degree of uniformity in size and shape, and that have dimensions such that the ratio of work size length to work size width is approximately 1:1, 2:1 or 3:1.

PB

PB: CLAY PAVERS

Clay pavers that are selected or produced for their durability and for their uniformity in size and shape.